





| SW_Product Name_Packaging Type | | H |
|---|--|--|
| Manufacturer: XXXXXXX | Product Art: | ADD GRAYSCALE IMAGE OF PRODUCT HERE |
| OXO Designer: XXXXXXX | | |
| Created: XXXXXXX | | |
| Modified: XXXXXXX | | |
| OXO Production: XXXXXXX | | |
| Modified: XXXXXXX | | |
| Material, Size, Ink Specs | | |
| Configuration: Card | Size: XX.XX in x XX.XX in | |
| Print Materials: Thin Card – Clay coated newsback – 0.9 mm thick | Process Inks:  | |
| Sided: 2 | | |
| Colors: 6/6 | | |
| Varnish/Lam: Matte Varnish (oil) | Pantone Inks:  | |
| Material without Printing: | | |
| Glue – Industrial Strength | | |
| Twist Ties – 1 flat clear twist tie [upper die holes] 1 flat black twist tie [lower die hole] | | |
| Clear Plastic Blade Cover – PP | | |
| Additional Specs | | |
| Testing Required: Bar Code Drop Testing | | |
| Testing N/A: Accelerated Age Tear | | |
| Notes: – The OXO logo should be printed correctly without distortion. – The above line art should be used for the Inner/Master Carton stickers. – Each finished package must hang straight. You may adjust the placement of the hanging hole (from left to right only) if necessary. – Do not print the purple line around the UPC bar code. – All inner cartons must have a top sheet of corrugated placed inside so that the packaging is not damaged when the cartons are sliced open with a knife. – A top sheet of corrugated cardboard is not needed if the inner carton is designed so that the products and packaging cannot be damaged when slicing open the carton with a knife. – The purple points are for Dennison for artwork reference, there is no die cut hole when making the card. – No PVC. | | |

Please update Spec Box info with Material, Size and NOTES details from approved APO Dieline in FINAL Configuration Folder.



| SW_Product Name_Packaging Type | | H |
|---|---------------------------------|--|
| Manufacturer: XXXXXXX | Product Art: | ADD GRAYSCALE IMAGE OF PRODUCT HERE |
| OXO Designer: XXXXXXX | | |
| Created: XXXXXXX | | |
| Modified: XXXXXXX | | |
| OXO Production: XXXXXXX | | |
| Modified: XXXXXXX | | |
| Material, Size, Ink Specs | | |
| Configuration: Card | Size: FLAT: XX.XX in x XX.XX in | |
| Print Materials: Thin Card – Clay coated newsback – 0.9 mm thick | Size: TRIM: XX.XX in x XX.XX in | |
| Sided: 2 | Process Inks: | |
| Colors: 6/6 | Pantone Inks: | |
| Varnish/Lam: Matte Varnish (oil) | | |
| Material without Printing: | | |
| Glue – Industrial Strength | | |
| Twist Ties – | | |
| 1 flat clear twist tie [upper die holes] | | |
| 1 flat black twist tie [lower die hole] | | |
| Clear Plastic Blade Cover – PP | | |
| Additional Specs | | |
| Testing Required: Bar Code Drop Testing | | |
| Testing N/A: Accelerated Age Tear | | |
| Notes: | | |
| – The OXO logo should be printed correctly without distortion. | | |
| – The above line art should be used for the Inner/ Master Carton stickers. | | |
| – Each finished package must hang straight. You may adjust the placement of the hanging hole (from left to right only) if necessary. | | |
| – Do not print the purple line around the UPC bar code. | | |
| – All inner cartons must have a top sheet of corrugated placed inside so that the packaging is not damaged when the cartons are sliced open with a knife. | | |
| – A top sheet of corrugated cardboard is not needed if the inner carton is designed so that the products and packaging cannot be damaged when slicing open the carton with a knife. | | |
| – The purple points are for Dennison for artwork reference, there is no die cut hole when making the card. | | |
| – No PVC. | | |

Please update Spec Box info with Material, Size and NOTES details from approved APO Dieline in FINAL Configuration Folder.



SW_Product Name_Packaging Type **H**

Manufacturer: XXXXXXXX Product Art:
 OXO Designer: XXXXXXXX
 Created: XXXXXXXX
 Modified: XXXXXXXX
 OXO Production: XXXXXXXX
 Modified: XXXXXXXX

**ADD
GRAYSCALE
IMAGE OF
PRODUCT
HERE**


Material, Size, Ink Specs


Configuration: Card Size: FLAT: XX.XX in x XX.XX in
 Print Materials: Thin Card – Size: TRIM: XX.XX in x XX.XX in
 Clay coated newsback
 – 0.9 mm thick

Sided: 2

Colors: 6/6

Varnish/Lam: Matte Varnish (oil)

Process Inks:


 Pantone Inks:


Material without Printing:

Glue – Industrial Strength

Twist Ties –
 1 flat clear twist tie [upper die holes]
 1 flat black twist tie [lower die hole]

Clear Plastic Blade Cover – PP



Additional Specs

Testing Required: Bar Code
 Drop Testing

Testing N/A: Accelerated Age
 Tear

Notes:

- The OXO logo should be printed correctly without distortion.
- The above line art should be used for the Inner/Master Carton stickers.
- Each finished package must hang straight. You may adjust the placement of the hanging hole (from left to right only) if necessary.
- Do not print the purple line around the UPC bar code.
- All inner cartons must have a top sheet of corrugated placed inside so that the packaging is not damaged when the cartons are sliced open with a knife.
- A top sheet of corrugated cardboard is not needed if the inner carton is designed so that the products and packaging cannot be damaged when slicing open the carton with a knife.
- The purple points are for Dennison for artwork reference, there is no die cut hole when making the card.
- No PVC.



Please update Spec Box info with Material, Size and NOTES details from approved APO Dieline in FINAL Configuration Folder.

SW_Product Name_Packaging Type

H

Manufacturer: XXXXXXXX Product Art:
OXO Designer: XXXXXXXX
Created: XXXXXXXX
Modified: XXXXXXXX
OXO Production: XXXXXXXX
Modified: XXXXXXXX

**ADD
GRAYSCALE
IMAGE OF
PRODUCT
HERE**

Material, Size, Ink Specs

Configuration: Hanging Card Size: FLAT: XX.XX in x XX.XX in
Print Materials: Bright White Solid Bleach Sulfate 0.45 mm Thick Size: TRIM: XX.XX in x XX.XX in
Sided: 2
Colors: 6/2
Varnish/Lam: Matte Varnish (oil)

Process Inks:
Cyan Magenta Yellow Black

Pantone Inks:
PMS 485 PMS CG10

Material without Printing:

Glue – Industrial Strength



Additional Specs

Testing Required: Bar Code
Drop Testing

Testing N/A: Accelerated Age
Tear

Notes:

- The OXO logo should be printed correctly without distortion.
- The above line art should be used for the Inner/Master Carton stickers.
- Each finished package must hang straight. You may adjust the placement of the hanging hole (from left to right only) if necessary.
- Do not print the purple line around the UPC bar code.
- All inner cartons must have a top sheet of corrugated placed inside so that the packaging is not damaged when the cartons are sliced open with a knife.
- A top sheet of corrugated cardboard is not needed if the inner carton is designed so that the products and packaging cannot be damaged when slicing open the carton with a knife.
- The purple points are for Dennison for artwork reference, there is no die cut hole when making the card.
- No PVC.



Please update Spec Box info with Material, Size and NOTES details from approved APO Dieline in FINAL Configuration Folder.

Alternate back on white